



"The Diamond of the Industry"

## Non-Metallic Strain Relief Cord Connectors Size Range 1/2" to 1"

- Utilized with portable cord to provide strain relief termination
- For use in wet or dry locations
- Oil, water, dust, resistant NEMA 4X IP68
- Stands up to most industrial corrosive environments
- Extended cord range to reduce inventory
- Tightening on nut creates a watertight seal
- Neoprene bushings cover a large cable range, reducing the number of different sized fittings required

Material: Type 6/6 Nylon      Color: Industrial Grey  
Sealing Grommet: Neoprene  
Temperature Range: -30° to 105°C Short Term: 150°C  
Flame Resistance: UL 94vo, incandescent Wire

UL Standard 514B • CUL to CSA Standard C22.2 No.18  
Environmental Rating: IP68 • NEMA 4X Watertight



| Cat. #  | Size | Unit Qty | Std. Pkg. | Wt./per 100 |
|---------|------|----------|-----------|-------------|
| NMCG50  | 1/2" | 25       | 125       | 3           |
| NMCG75  | 3/4" | 10       | 100       | 6           |
| NMCG100 | 1"   | 10       | 100       | 9           |

| Cat. #  | Size | Cable Ranges<br>Min. - Max. | A      | B     | C      |
|---------|------|-----------------------------|--------|-------|--------|
| NMCG50  | 1/2" | .236 - .472                 | 1.968" | .590" | .945"  |
| NMCG75  | 3/4" | .472 - .709                 | 2.007" | .590" | 1.299" |
| NMCG100 | 1"   | .669 - .984                 | 2.401" | .748" | 1.653" |

