



"The Diamond of the Industry"

Liquid Tight Connectors Grounding Type with Aluminum Lugs

- A quick, effective solution to connecting liquid tight conduit while terminating a bonding connector in one action
- Sleek screw machined bodies and nuts promote easy installation
- Strong construction and long ferrule prevent pullouts
- All components are reusable
- Furnished with locknut and sealing washer

Straight Connectors with Insulated Throat

| Cat. # | Size | Unit Ctn | Std Pkg | WT/100 |
|-----------|--------|----------|---------|--------|
| STR38BGL | 3/8" | 25 | 125 | 12 |
| STR50BGL | 1/2" | 25 | 125 | 15 |
| STR75BGL | 3/4" | 25 | 125 | 20 |
| STR100BGL | 1" | 10 | 50 | 34 |
| STR125BGL | 1-1/4" | 5 | 25 | 46 |
| STR150BGL | 1-1/2" | 5 | 25 | 68 |
| STR200BGL | 2" | 2 | 10 | 87 |
| STR250BGL | 2-1/2" | - | 5 | 267 |
| STR300BGL | 3" | - | 4 | 367 |
| STR350BGL | 3-1/2" | - | 3 | 464 |
| STR400BGL | 4" | - | 2 | 539 |

Straight Connectors

| Cat. # | Size | Unit Ctn | Std Pkg | WT/100 |
|----------|--------|----------|---------|--------|
| STR38GL | 3/8" | 25 | 125 | 12 |
| STR50GL | 1/2" | 25 | 125 | 15 |
| STR75GL | 3/4" | 25 | 125 | 20 |
| STR100GL | 1" | 10 | 50 | 34 |
| STR125GL | 1-1/4" | 5 | 25 | 46 |
| STR150GL | 1-1/2" | 5 | 25 | 68 |
| STR200GL | 2" | 2 | 10 | 87 |
| STR250GL | 2-1/2" | - | 5 | 267 |
| STR300GL | 3" | - | 4 | 367 |
| STR350GL | 3-1/2" | - | 3 | 464 |
| STR400GL | 4" | - | 2 | 539 |

Dimensional Table

| Cat. # | A Diameter | B Overall Length | C Length of Thread | D Length of Lug |
|----------|---------------|---------------------|-----------------------|--------------------|
| STR38GL | 1.09 | 1.19 | .63 | .750 |
| STR50GL | 1.19 | 1.34 | .63 | .750 |
| STR75GL | 1.43 | 1.43 | .63 | .750 |
| STR100GL | 1.75 | 1.63 | .66 | .750 |
| STR125GL | 2.16 | 1.84 | .67 | .750 |
| STR150GL | 2.38 | 2.00 | .72 | .750 |
| STR200GL | 2.88 | 2.13 | .72 | .750 |
| STR250GL | 4.00 | 3.25 | 1.50 | 1.093 |
| STR300GL | 4.63 | 3.88 | 1.50 | 1.093 |
| STR350GL | 5.50 | 4.00 | 1.50 | 1.687 |
| STR400GL | 5.82 | 4.00 | 1.63 | 1.687 |

UL rated suitable for hazardous locations.
Class I, Div. 2; Class II, Div. 1 and 2;
Class III, Div. 1 and 2; NEC 501-4(b), 502-4(a), 503-3(a)

